

C&L SUPER BIKE 4T SL/MA2

SYNTHETIC 4T ENGINE OIL



DESCRIPTION

Excellent performance, shear-stable, multi-grade gasoline engine oil specially formulated for use in 4-stroke motorcycles and portable power equipment requiring API SL, JASO MA2 lubricants, including high output engines operating in severe condition.

CHARACTERISTICS

- Prolongs engine life by reduced wear under highly stressed engine components
- Highly shear stable VI improver minimizes shear-thinning, particularly in the gearbox
- Balanced additive formula ensures excellent control of piston ring deposit under severe operation condition
- Save maintenance cost by high oxidation stability which resists oil breakdown under the severe heat stress generated by modern engines

PERFORMANCE LEVEL

20W-50

API SL
JASO MA2

TYPICAL PROPERTIES

		20W-50
Density @ 15°C	g/cm ³	0.870
Viscosity @ 100°C	mm ² /s	19.5
CCS	cP	<9500
Viscosity Index		145
Flash Point	°C	240
Pour Point	°C	-24



0.8L 1L
AVAILABLE

This data is for your reference and it can't be used for any legal purpose.



C AND LUBE CO., LTD.
182 Hwasan-ro, Ulju-gun, Ulsan, Korea
www.cnlube.co.kr
Tel.+82-10-3522-2172
sales@cnlube.co.kr