

C&L SUPER BIKE 4T SL/MB

SYNTHETIC 4T ENGINE OIL



DESCRIPTION

Super Bike 4T SL/MB is a specially made to meet the latest technology scooters and mopeds requiring API SL and JASO MB specification. Super Bike 4t SL/MB is made by well balanced formulation for excellent engine protection and trouble free operation.

CHARACTERISTICS

- Easy start-up with reduces friction
- Maximum lubrication under high-temperature operation
- Maintain engine power and cleanliness
- Reduce the piston blow-by gas to minimize sludge forming
- Excellent shear stability and maximum wear protection in high speed & temp operation
- Prolonged engine life
- Extended oil drainage interval.

PERFORMANCE LEVEL

10W-40

API SL
JASO MB

TYPICAL PROPERTIES

		10W-40
Density @ 15°C	g/cm ³	0.865
Viscosity @ 100°C	mm ² /s	14.0
CCS	cP	<7000
Viscosity Index		145
Flash Point	°C	225
Pour Point	°C	-36



**0.8L 1L
AVAILABLE**

This data is for your reference and it can't be used for any legal purpose.



C AND LUBE CO., LTD.
182 Hwasan-ro, Ulju-gun, Ulsan, Korea
www.cnlube.co.kr
Tel.+82-10-3522-2172
sales@cnlube.co.kr