C&L SOLAR EP GREASE EXTREME PRESSURE GREASE



DESCRIPTION

Solar EP Grease is desidesigned for multi-purpose with extreme pressure application. It is made of lithium thickener and highly refined mineral base oils. Mainly recommended for automotive application such as wheel bearing, chassis as well as industrial application requires shock load or extreme pressure.

CHARACTERISTICS

- Multi-purpose application where EP property required
- · Excellent load carrying capability and base metal protection
- Long service life by outstanding mechanical stability
- Effective anti-rust and anti-corrosion
- \cdot Severe conditions under shock loading and wet conditions
- · For Heavy duty bearings and general industrial lubrication

PERFORMANCE LEVEL

EP GREASE NLGI 00 - 3

TYPICAL PROPERTIES

| NLGI Grade | 00 | 2 | 3 |
|--------------------------------|---------|---------|---------|
| Color | Brown | Brown | Brown |
| Thickener | Li Soap | Li Soap | Li Soap |
| Worked Penetration (25°C,60 W) | 410 | 280 | 235 |
| Dropping Point, °C | 160 | 200 | 210 |
| Copper corrosion | NC | NC | NC |

This data is for your reference and it can't be used for any legal purpose.



15KG 180KG AVAILABLE

C AND LUBE CO., LTD. 182 Hwasan-ro, Ulju-gun, Ulsan, Korea www.cnlube.co.kr Tel.+82-10-3522-2172 sales@cnlube.co.kr

