

C&L TAURUS GEAR OIL

INDUSTRIAL GEAR OIL



DESCRIPTION

C&L Taurus Gear oil is suitable for most of industrial gear operation. Selected base stocks and additives to provide longer gear system protection. Well balanced additive package provides best operation condition.

CHARACTERISTICS

- Protect gears from heavy and shock load operation
- Excellent heat stability prevents contaminant from sticking on gear surface
- Stable viscosity under high temperature
- Compatible with metal or non-metal material
- Protect equipment from water particle existence
- Long service life
- For most of industrial gears requiring EP property

PERFORMANCE LEVEL

INDUSTRIAL GEAR OIL

US Steel 224
AGMA 250.04
DIN 51517 Part3

TYPICAL PROPERTIES

ISO VG		150	220	320	460
Density @ 15°C	g/cm ³	0.880	0.890	0.890	0.895
Viscosity @ 100°C	mm ² /s	150	220	320	460
Viscosity Index		105	100	95	95
Flash Point	°C	240	250	245	260
Pour Point	°C	-15	-12	-12	-12

This data is for your reference and it can't be used for any legal purpose.



**20L 200L
AVAILABLE**



C AND LUBE CO., LTD.
182 Hwasan-ro, Ulju-gun, Ulsan, Korea
www.cnlube.co.kr
Tel.+82-10-3522-2172
sales@cnlube.co.kr